



VICINITY MAP

PROJECT DESCRIPTION:
CONSTRUCT NEW 4,000 SF CONVENIENCE STORE W/4 GAS PUMPS (8 PUMP STATIONS) AND 11,901 SF OF RETAIL/COMMERCIAL SPACE WITH ASSOCIATED PARKING, PAVING, & STORM WATER RETENTION. THE NEW STORE WILL BE ORDINARY TYPE V CONSTRUCTION, UNPROTECTED, UNSPRINKLED, MASONRY WALLS WITH PRE-ENGINEERED WOOD TRUSSES.

OWNER:
EMEN INTERNATIONAL INC.
1200 MALABAR RD, UNIT 3
PALM BAY, FL 32907
PHONE: (321) 259-8400
FAX: (321) 254-4568
CONTACT: HEM GANDHI

ENGINEER:
M.E. CONSTRUCTION, INC.
7606 CORAL DRIVE
WEST MELBOURNE, FL 32904
PH. (321) 723-5681
FAX: (321) 951-1952
CONTACT: MR. STEVE MONROE, P.E.

LEGAL DESCRIPTION: SEE C-2
TOTAL AREA OWNED: = 92,825 SF = 2.126 AC = 100% (NO EXISTING STRUCTURES)
TAX ID#: 29-37-05-Gu-00005.0-0000.00
ZONING: NC **LAND USE DESIGNATION:** NEIGHBORHOOD COMMERCIAL
ADJACENT ZONING: NORTH RS-1 EAST RS-1 SOUTH IU WEST NC
CONSTRUCTION TYPE: TYPE IV, MASONRY WALLS, WOOD TRUSS, UNSPRINKLED
CURRENT USE: VACANT LOT
MAX ALLOW BUILDING HEIGHT: 25'-0"
PROPOSED BUILDING HEIGHT: BUILDING = EAVE = 12'-4" RIDGE = 22'-7"
CANOPY = 15'-0" (14'-0" CLEARANCE)

SETBACKS

BUILDING	REQUIRED	PROVIDED
NORTH	25'	843.5'
SOUTH	75'	±123.5'
EAST	25'	±26'
WEST	75'	±76.9'

CANOPY & PUMPS AND ASSOCIATED AREAS	REQUIRED	PROVIDED
NORTH	100'	±215.5'
SOUTH	20'	±20'
EAST	20'	±174'
WEST	20'	±63'

PARKING/PAVING	REQUIRED	PROVIDED
NORTH	20'	±25.3'
SOUTH	10'	10'
EAST	10'	10'
WEST	10'	10'

PARKING REQUIREMENTS:

USE	SF	SPACES/SF	REQ
CONVENIENCE STORE	4,000	1/200 SF	20
RETAIL SPACE	11,901	1/200 SF	60
TOTAL REQUIRED PARKING (INC 4 H/C)			80 SPACES

PARKING PROVIDED: 80 SPACES (INC 4 H/C) + 8 FUELING POSITIONS
EXISTING IMPERVIOUS AREAS: VACANT LAND
PROPOSED IMPERVIOUS AREAS:

AREA	SF	AC	%
BUILDING	15,901	0.365	17.2
PARKING/ PAVING	39,538	0.908	42.7
SIDEWALK	5,764	0.132	6.2
TOTAL	61,203	1.405	66.1

TOTAL PERVIOUS AREA: = 31,422 SF = 0.721 AC = 33.9%

NOTES:
1) CITY OF PALM BAY SITE PLAN APPROVAL REQUIRED.
2) ST. JOHNS WATER MANAGEMENT DISTRICT PERMIT REQUIRED.
3) CITY OF PALM BAY DRIVEWAY PERMIT REQUIRED FOR EACH DRIVEWAY. (2 TOTAL)
4) UNDERGROUND STORAGE REQUIRED FOR COMBUSTABLE MATERIALS IN EXCESS OF 200 GALLONS.
5) WATER FOR FIRE FIGHTING PURPOSES SHALL BE AVAILABLE PRIOR TO COMBUSTIBLES BEING BROUGHT ON SITE.
△ 6) DELETED.
7) FIRE HYDRANTS SHALL BE LOCATED NOT FARTHER THAN EIGHT FEET NOR LESS THAN THREE FEET FROM AN IMPROVED SURFACE.
△ 8) EVERY BUILDING SHALL BE ACCESSIBLE TO FIRE DEPARTMENT APPARATUS BY WAY OF ACCESS ROADS CONSTRUCTED OF HARD, ALL-WEATHER DRIVING SURFACE OF NOT LESS THAN 20 FEET WIDE AND HAVING A 13 FOOT 6 INCH VERTICAL CLEARANCE. ACCESS ROADS SHALL BE MAINTAINED IN A SERVICEABLE MANNER ACCEPTABLE TO THE FIRE DEPARTMENT. ACCESS ROADS IN EXCESS OF 150 FEET SHALL BE PROVIDED WITH APPROVED PROVISIONS FOR THE TURNING AROUND OF FIRE APPARATUS. NFPA 241, 5-4.3. APPLIES TO CANOPY & STRIPED YELLOW MEDIANS IF RAISED.
9) THE FIRE INSPECTOR SHALL WITNESS THE FOLLOWING INSPECTIONS FOR NEW FUEL TANKS PRIOR TO FINAL APPROVAL: A) LOCATION, B) DEPTH, C) ANCHORING METHOD, D) DISPENSER, E) COVER. CONTRACTOR MUST SUBMIT FORM 17-61.090 (5) TO D.E.R. (DEPARTMENT OF ENVIRONMENTAL REGULATIONS) FOR POLLUTANT STORAGE TANK INSTALLATION PROGRAM WITHIN 30 DAYS OF COMPLETION OF THE TANK INSTALLATION.
10) PUMPS AT AN ATTENDANT STORAGE TANKS SHALL BE CONSPICUOUSLY POSTED WITH THE FOLLOWING WORDING: A) WARNING – IT IS UNLAWFUL AND DANGEROUS TO DISPENSE GASOLINE INTO UNAPPROVED CONTAINERS, B) NO SMOKING, C) STOP MOTOR. NFPA 30A,6-9
11) INSTALL APPROVED ADDRESS IDENTIFICATION PLAINLY LEGIBLE AND VISIBLE FROM THE STREET OR ROAD FRONTING THE PROPERTY. THE NUMBERS SHALL CONTRAST WITH THEIR BACKGROUND AND BE AT LEAST 6" IN HEIGHT. NFPA 1, 9-7.1
12) LANDSCAPING WITHIN SIGHT DISTANCE TRIANGLE SHALL BE IN ACCORDANCE WITH FDOT INDEX #546.
13) SIGNAGE & PAVEMENT MARKINGS TESTS SHALL BE SUBMITTED TO THE CITY OF PALM BAY. SEE COVER FOR ADDITIONAL INFORMATION.
14) THERE IS NO INTERSECTION OF COLLECTOR STREETS OR HIGHER CLASSIFICATION WITHIN 100' OF NORTH OR WEST PROPERTY CORNERS.
15) NO MUNICIPLE OR PUBLIC SUPPLY WELL WITHIN 1000FT OF ONSITE GASOLINE FUEL DISPENSING FACILITY. NFPA 30A, 2-3.2.2
16) DIMENSIONS SHOWN ARE TO / FROM FACE OF CURB
17) SIDE SLOPES OF RETENTION AREA AND SLOPES GREATER THAN 3:1 SHALL BE SODDED
18) SIDEWALKS MUST MEET CITY OF PALM BAY STANDARDS. CROSS-SECTIONS & PROFILES SHALL BE MAINTAINED. SIDEWALKS SHALL BE 5' TO 8' WIDE WITH MAX. TRANSVERSE SLOPE OF 2% AND A MAX. CROSS SLOPE OF 2%.
19) DEVELOPMENT & OPERATION OF FUEL PUMPS & ATTENDANT STORAGE TANKS SHALL COMPLY WITH ALL APPLICABLE LAWS, WITH CHAPTER 176 OF PALM BAY CODE OF ORDINANCE.
20) ACCESS ROADWAYS SHALL NOT BE OBSTRUCTED IN ANY MANNER, INCLUDING OBSTRUCTION BY PARKED VEHICLES. NFPA 241, 7-2.1.1
21) ALL PAVEMENT MARKINGS AND SIGNS SHALL BE THE PERPETUAL MAINTENANCE RESPONSIBILITY OF THE OWNER OR ASSIGNS.
△ 22) FIRE HYDRANTS AND APPLIANCES SHALL BE KEPT ACCESSIBLE TO THE FIRE DEPARTMENT AT ALL TIMES. A CLEARANCE OF SEVEN AND ONE HALF FEET IN FRONT OF AND TO THE SIDES OF FIRE HYDRANTS AND APPLIANCES SHALL BE MAINTAINED. CLEARANCE OF FOUR FEET TO THE REAR OF FIRE HYDRANTS SHALL BE MAINTAINED.
23) GATES AT THE SIDEWALKS SHALL MEET THE REQUIREMENTS FOR LOCKS AND LATCHES ON EXIT DOORS WHENEVER THE BUILDING IS OCCUPIED.

COPYRIGHT © STATEMENT
THESE DOCUMENTS AND THEIR CONTENTS ARE THE PROPERTY OF M. E. CONSTRUCTION, INC (MEC) AND ARE ISSUED ONLY FOR THE SPECIFIC PROJECT NOTED ON THESE DOCUMENTS. ANY REVISIONS, REPRODUCTIONS OR MODIFICATIONS OF THESE DOCUMENTS WITHOUT THE EXPRESS WRITTEN CONSENT OF MEC IS PROHIBITED BY LAW.

SITE PLAN APPROVED
CITY OF PALM BAY, FLORIDA
DEVELOPMENT SERVICES DEPARTMENT
10/17/07
DATE

M.E. Construction, Inc.
7607 Coral Drive, West Melbourne, FL 32904
(321) 723-5669 Fax(321) 951-1952
Engineering # 7219 General Contracting # 2379

PROJECT NAME
EMERSON & JUPITER CONVENIENCE STORE
SHEET DESCRIPTION
SITE PLAN
DRAWING SCALE
1=20'
DATE OF ORIGINAL ISSUE: 12/21/05 DRAWN: KB CHECKED: SM APPR: SM

REV.	DATE	BY	DESCRIPTION
△	4/13/06	SM	REVISED PER CITY OF PALM BAY
△	5/7/06	SM	REVISED PER CITY OF PALM BAY
△	8/28/07	SM	REVISED SIDEWALK ALONG JUPITER BLVD.

PROJECT NUMBER
30486
SHEET 4 OF 10
C-3